

ROTEL

STEREO INTEGRATED AMPLIFIER

A14



2 x 80 Watts
of robust Class
AB power



iOS / Android
control App



Moving magnet
phono input for
turntable connection



Integrated
Bluetooth aptX



AKM premium 32-bit/
768kHz Digital to Analog
Converter

The flagship A14 has the highest power and widest set of features in the range. The A14 is rated at 80 watts per channel RMS into 8 ohms, both channels driven. Yet ratings alone do not reflect real world usage. The A14 features a rugged power supply comprising a Rotel-manufactured toroidal transformer plus slit-foil capacitors to effortlessly handle difficult speaker

loads and dynamic signal peaks. This is an impressively flexible audio component, designed to accommodate both classic analogue and the latest digital source components supported by the on-board AKM 32 bit/768kHz DAC. But its greatest strength lies in its ability to render a musical performance exactly as the artist intended.

Rotel integrated
amplifiers bring your
sources to life with
amazing fidelity.
See more at

rotel.com



STEREO INTEGRATED AMPLIFIER

A14



SPECIFICATIONS

Continuous Power Output (20 - 20kHz, < 0.03%, 8 ohms)	80 watts/ch	Digital Section	
Total Harmonic Distortion (20 Hz - 20 kHz at rated power)	< 0.03%	Frequency Response	10Hz - 80kHz (± 3.0dB, MAX)
Intermodulation Distortion (60 Hz : 7kHz, 4:1)	< 0.03%	Signal to Noise Ratio (IHF "A" weighted)	103 dB
Frequency Response		Input Sensitivity/Impedance	0 dBfs/75 Ohms
Phono Input	20Hz - 15kHz, ± 0.5dB	Preamplifier Output Level	1.3 V (at - 20dB)
Line Level Inputs	10Hz - 100kHz, ± 0.5dB	Digital Inputs	SPDIF LPCM (up to 192kHz / 24 bit)
Damping Factor (20 - 20,000 Hz, 8 ohms)	220	PC-USB	USB Audio Class 1.0 (up to 96kHz 24bit) USB Audio Class 2.0 (up to 384kHz 32bit)* *Driver installation required DSD and DoP support
Input Sensitivity / Impedance		General	
Phono Input	3.4 mV / 47k Ohms	Power Requirements	
Line Level Inputs	230 mV / 24k Ohms	Europe	230V, 50Hz
Input Overload		USA	120V, 60Hz
Phono Input	50 mV	Power Consumption	280 watts
Line Level Inputs	4 V	Standby Power Consumption	< 0.5 watts
Preamp Output / Impedance	1.2 V / 470 Ohms	Finishes	Silver and Black
Tone Controls - Bass / Treble	± 10 dB at 100Hz / 10kHz	Dimensions (W x H x D)	430 x 93 x 345mm 17" x 3 5/8" x 13 1/2"
Signal to Noise Ratio ("A" weighting)		Front Panel Height	80mm, 3 1/8"
Phono Input	90 dB	Weight (net)	8.2kg, 18 lb
Line Level Inputs	100 dB		

Rotel integrated amplifiers bring your sources to life with amazing fidelity. See more at

rotel.com

