The life of sound.

Miracord[™] 50 Turntable

Smooth vinyl precision.

ELAC's Miracord 50 Turntable is designed to deliver exceptional vinyl transcription, inspired by the iconic Miracord name from the Golden Age of Stereo, when turntables reigned supreme. The Miracord 50 is carefully engineered with a belt-drive motor and die-cast aluminum platter. A precision static-balanced, straight-tube tonearm with removable headshell features a factory-mounted MM phono cartridge. Designed with convenience in mind, the Miracord 50 is equipped with a built-in defeatable phono preamplifier, allowing you to add this turntable to any music system.



Miracord 50 Turntable

The warmth of analog sound.

The resurgence of vinyl has created a groundswell of enthusiasm among audiophiles and music enthusiasts who have never before enjoyed the thrill of spinning an LP! The Miracord 50 is the perfect choice for those building a new LP collection, or for rediscovering the magic of an existing record library.

11RACORD 50 TURNTABLE FEATURES

ti-resonant Chassis

perior isolation is achieved with a chassis signed to minimize the sonic effects of ration and feedback. A low-noise DC vo motor drives a die-cast, high-inertia minum platter with special record mat a rubber belt, resulting in stable speed minimal wow and flutter.

cision Tonearm and Cartridge

tonearm is a static-balance, straighte design with precision bearings, builtnti-skate adjustment and removable onet-style headshell. A premounted moving-magnet cartridge takes all the guesswork out of setup and assures proper vertical tracking angle, tracking weight and azimuth adjustment right out of the box.

Built-in Phono Equalizer Amplifier

Unlike most turntables, the Miracord 50 comes complete with a built-in defeatable phono preamp for correct RIAA equalization. That means you can add LP playback without having to add a costly phono stage to line-level preamps or digital-only systems. Just plug it in, put on a record and enjoy rich LP sound!

Contemporary Finish

Styled to complement any interior, the Miracord 50 is available with a silver chassis and gloss-black plinth. A hinged, tinted dustcover is included.



MIRACORD 50 TURNTABLE SPECIFICATIONS

TURNTABLE SECTION

Drive System
 Motor
 Selectable Speeds
 Belt drive
 DC motor
 Selectable Speeds
 33½ and 45 rpm

Motor Servo Speed rotation and servo system

Rotation Speed Variation +/-1% Wow and Flutter 0.1%

Signal-to-Noise Ratio -67 dB or higher (A-weighted) -60 dB or higher (unweighted)

Platter Aluminum die-cast
 Platter Diameter 12.0 in / 300 mm

TONEARM SECTION

 Type Aluminum tube, static-balanced · Effective Arm Length 8.8 in / 223.6 mm Stylus Pressure Range 0 to 4.0 g Cartridge Weight Range 3.5 to 6.0 g Effective Arm Mass 27.4 g Overhang 18.6 mm Offset Angle 25 degrees Anti-Skating Adjustment Supported Main Bearing Stainless steel

CARTRIDGE SECTION

Type Audio-Technica AT91 moving magnet
 Stylus Construction Bonded diamond
 Mount Half-inch
 Frequency Response 20 Hz to 20 kHz
 Channel Separation >18 dB
 Channel Balance 2.5 dB

Channel Balance 2.5 dB
Vertical Tracking Angle 20 degrees
Stylus Pressure 2.0 g +/-0.5 g
Cartridge Weight 5.0 g +/-0.5 g

Headshell Weight 11.0 g (including screws, nuts and wires)

PHONO EQUALIZER AMPLIFIER

Type Moving magnet (MM)
Phono Output 2.5 mV (1 kHz, 3.54 cm/sec)
Line Output 140 mV (-17 dBV)
Phono/Line Switchable
Supported Load Impedance

CONNECTOR
VOLTAGE
POWER CONSUMPTION
DIMENSIONS (WXHXD)
WEIGHT

RCA pin jack including RCA cable accessories 100 to 240 V AC / 50 to 60 Hz 1.5 W (less than 0.5 W at standby) $5.5 \times 16.05 \times 14.20$ 12.10 lb



